WHIRLPOOL BRAND COMMERCIAL DRYERS

PORCELAIN FINISH

Porcelain finish on top with integrated backsplash, resists chipping and scratching.

LARGE CAPACITY METERCASE

- Larger coin box for reduced collections.
- Accepts coin slides, coin drops, card readers and can be set up for OPL non-coin use.

LARGE 6.7 CU. FT. DRUM CAPACITY

The increased capacity allows for large loads of clothes to tumble and spread out, saving you and your customers drying time and expense.

SIDE SWING REVERSIBLE OPENING DOOR

- Extra-large opening
- See through door window and screen

MICROPROCESSOR CONTROLS

- Time remaining display
- Front controls for ease-of-use
- Debit card compatible
- Time of Day Pricing

AIRFLOW SYSTEM

Whirlpool® commercial dryers blower system increases air velocity. This increases efficiency, heating element life, and improves installation. You can now vent up to 100 ft. with 3 elbows, and 1 angled hood for versatility.

4-WAY VENTING

4-Way venting from left or right side, back or bottom.

LARGE LINT FILTER

Pull-out, 84 square inch steel mesh lint filter.

1/3 HP MOTOR

1/3 HP motor with overload protection.

COMMERCIAL DRYER

Featuring Microprocessor Controls



Shown with optional pedestal, coin drop and box.

CEW9100VQ - 27" Electric Dryer with Metercase CGW9100VQ - 27" Gas Dryer with Metercase

Machine accepts the Following Payment Systems (not included):

- Coin Slide
- Retrofit Coin Drop
- Retrofit Card Reader
- OPL Non-Coin Money Acceptor And Coin Box Covers
- Large 6.7 Cu. Ft. Drum Capacity
- Four Roller Suspension with Permanently Lubricated Bearings
- Push Button Controls
- Large Lint Screen (84 Sq. In.)
- Blower Guard Reduces Service Calls
- Front Control Panel 24° Angle

- Side-Swing Reversible Door
- Porcelain Finish on Top with Backsplash Resists Chipping and Scratching
- Front-Service Accessibility
- Electric Heating Element at 5600 Watts 240-Volt
- Gas Model Features a 24K BTU Burner
- Motor: 1/3-HP with Built-In Overload Protector; Centrifugal Switch Turns Off Heating Element in the Event of a Broken Belt
- 3 Year Limited Parts Only Warranty
- Money Acceptors Sold Separately

^{*}Call 1-800-NO-BELTS for warranty details

COMMERCIAL DRYER SPECIFICATIONS

Whirlpool® Extra-Large Capacity Dryer MICROPROCESSOR CONTROLS


MODEL CEW9100VQ/CGW9100VQ MOTOR MOTOR Single-phase, thermoprotected against overload, auto-reset 1/3 (.25) HP (kw) 1/3 (.25) CAPACITY 6.7 (189.7) DOOR OPENING DIAMETER In. (mm) In. (mm) 18.25 (463.5) AIRFLOW 230 (6.5) Gas models — cfm (cmm) 215 (6.1) ELECTRICAL REQUIREMENTS CEW model — voltage CGW model — voltage 120V/60Hz BREAKER/FUSE REQUIREMENTS CEW model — amps CEW model — amps 30 CGW model — amps 15 EXHAUST DUCT DIAMETER In. (mm) GW model — BTU/hr. (kcal/hr.) 24,000 (6,048) CEW model — BTU/hr. (kcal/hr.) 24,000 (6,048) CEW model — Electric Heating Element - watts 5,600 GAS INLET CGW model — in. CGW model — in. 3/8 N.P.T. ADJUSTABLE LEVELING LEGS • APPROXIMATE WEIGHT Crated — lbs. (kg) 163 (73.9) Uncrated — lbs. (kg) 150 (68) DIMENSIONS 150 (68)	DRYER SPECIFICATIONS	
Single-phase, thermoprotected against overload, auto-reset HP (kw) CAPACITY Cu. ft. (liters) DOOR OPENING DIAMETER In. (mm) 18.25 (463.5) AIRFLOW Gas models — cfm (cmm) ELECTRICAL REQUIREMENTS CEW model — voltage BREAKER/FUSE REQUIREMENTS CEW model — amps CGW model — amps SCW model — amps EXHAUST DUCT DIAMETER In. (mm) 4 (101.6) ELECTRONIC BURNER IGNITION CGW model — BTU/hr. (kcal/hr.) CEW model — in. ADJUSTABLE LEVELING LEGS APPROXIMATE WEIGHT Crated — lbs. (kg) Incrated — lbs. (kg) IMMISSIONS Width — in. (mm) VA (189.7) 18.25) 6.7 (189.7) 18.26) 24.63.5) 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18.27 18	MODEL	CEW9100VQ/CGW9100VQ
auto-reset HP (kw)	MOTOR	
HP (kw) 1/3 (.25) CAPACITY Cu. ft. (liters) 6.7 (189.7) DOOR OPENING DIAMETER In. (mm) 18.25 (463.5) AIRFLOW Gas models — cfm (cmm) 230 (6.5) Electric models — cfm (cmm) 215 (6.1) ELECTRICAL REQUIREMENTS CEW model — voltage 240V/60Hz CGW model — voltage 120V/60Hz BREAKER/FUSE REQUIREMENTS CEW model — amps 30 CGW model — amps 15 EXHAUST DUCT DIAMETER In. (mm) 4 (101.6) ELECTRONIC BURNER IGNITION CGW model — BTU/hr. (kcal/hr.) 24,000 (6,048) CEW model — Electric Heating Element - watts 5,600 GAS INLET CGW model — in. 3/8 N.P.T. ADJUSTABLE LEVELING LEGS • APPROXIMATE WEIGHT Crated — lbs. (kg) 163 (73.9) Uncrated — lbs. (kg) 150 (68) DIMENSIONS Width — in. (mm) 27 (685.8)	Single-phase, thermoprotected against overload,	
CAPACITY Cu. ft. (liters) 6.7 (189.7) DOOR OPENING DIAMETER In. (mm) 18.25 (463.5) AIRFLOW Gas models — cfm (cmm) 230 (6.5) Electric models — cfm (cmm) 215 (6.1) ELECTRICAL REQUIREMENTS CEW model — voltage 240V/60Hz CGW model — voltage 120V/60Hz BREAKER/FUSE REQUIREMENTS CEW model — amps 30 CGW model — amps 15 EXHAUST DUCT DIAMETER In. (mm) 4 (101.6) ELECTRONIC BURNER IGNITION CGW model — BTU/hr. (kcal/hr.) 24,000 (6,048) CEW model — Electric Heating Element - watts 5,600 GAS INLET CGW model — in. 3/8 N.P.T. ADJUSTABLE LEVELING LEGS • APPROXIMATE WEIGHT Crated — lbs. (kg) 163 (73.9) Uncrated — lbs. (kg) 150 (68) DIMENSIONS Width — in. (mm) 27 (685.8)	auto-reset	
Cu. ft. (liters) 6.7 (189.7)	HP (kw)	1/3 (.25)
DOOR OPENING DIAMETER In. (mm)	CAPACITY	
In. (mm) AIRFLOW Gas models — cfm (cmm) Electric models — cfm (cmm) ELECTRICAL REQUIREMENTS CEW model — voltage CGW model — voltage BREAKER/FUSE REQUIREMENTS CEW model — amps GGW model — amps 15 EXHAUST DUCT DIAMETER In. (mm) 4 (101.6) ELECTRONIC BURNER IGNITION CGW model — BTU/hr. (kcal/hr.) CGW model — BTU/hr. (kcal/hr.) CEW model — Electric Heating Element - watts GAS INLET CGW model — in. ADJUSTABLE LEVELING LEGS APPROXIMATE WEIGHT Crated — lbs. (kg) Uncrated — lbs. (kg) DIMENSIONS Width — in. (mm) 230 (6.5) 2400/(6.1) 2400/(6.1) 2400/(6.048) 2500 2600 270685.8)	Cu. ft. (liters)	6.7 (189.7)
AIRFLOW Gas models — cfm (cmm) Electric models — cfm (cmm) ELECTRICAL REQUIREMENTS CEW model — voltage CGW model — voltage BREAKER/FUSE REQUIREMENTS CEW model — amps CGW model — amps EXHAUST DUCT DIAMETER In. (mm) ELECTRONIC BURNER IGNITION CGW model HEATING ELEMENT RATING CGW model — BTU/hr. (kcal/hr.) CEW model — Electric Heating Element - watts GAS INLET CGW model — in. ADJUSTABLE LEVELING LEGS APPROXIMATE WEIGHT Crated — lbs. (kg) DIMENSIONS Width — in. (mm) 230 (6.5) 240V/60Hz 30 30 CEW model — electric Heating Element - watts 5,600 63 INLET CGW model — in. 3/8 N.P.T. 40 163 (73.9) Uncrated — lbs. (kg) 150 (68) DIMENSIONS Width — in. (mm)	DOOR OPENING DIAMETER	
Cas models — cfm (cmm) 230 (6.5)	In. (mm)	18.25 (463.5)
Electric models — cfm (cmm) ELECTRICAL REQUIREMENTS CEW model — voltage CGW model — voltage BREAKER/FUSE REQUIREMENTS CEW model — amps CGW model — amps CGW model — amps EXHAUST DUCT DIAMETER In. (mm) ELECTRONIC BURNER IGNITION CGW model — BTU/hr. (kcal/hr.) CEW model — BTU/hr. (kcal/hr.) CGW model — Electric Heating Element - watts GAS INLET CGW model — in. ADJUSTABLE LEVELING LEGS APPROXIMATE WEIGHT Crated — lbs. (kg) DIMENSIONS Width — in. (mm) 215 (68.1) 24,000 (6,048) 24,000 (6,048) 163 (73.9) Uncrated — lbs. (kg) DIMENSIONS Width — in. (mm)	AIRFLOW	
ELECTRICAL REQUIREMENTS CEW model — voltage 240V/60Hz BREAKER/FUSE REQUIREMENTS CEW model — amps 30 CGW model — amps 15 EXHAUST DUCT DIAMETER In. (mm) 4 (101.6) ELECTRONIC BURNER IGNITION CGW model — BTU/hr. (kcal/hr.) 24,000 (6,048) CEW model — BTU/hr. (kcal/hr.) 24,000 (6,048) CEW model — Electric Heating Element - watts 5,600 GAS INLET CGW model — in. 3/8 N.P.T. ADJUSTABLE LEVELING LEGS • APPROXIMATE WEIGHT Crated — lbs. (kg) 163 (73.9) Uncrated — lbs. (kg) 150 (68) DIMENSIONS Width — in. (mm) 27 (685.8)	Gas models — cfm (cmm)	230 (6.5)
CEW model — voltage CGW model — voltage BREAKER/FUSE REQUIREMENTS CEW model — amps CGW model — amps EXHAUST DUCT DIAMETER In. (mm) ELECTRONIC BURNER IGNITION CGW model — BTU/hr. (kcal/hr.) CEW model — BTU/hr. (kcal/hr.) CEW model — Electric Heating Element - watts GAS INLET CGW model — in. ADJUSTABLE LEVELING LEGS APPROXIMATE WEIGHT Crated — lbs. (kg) DIMENSIONS Width — in. (mm) 24,000 (6,048) 163 (73.9) DIMENSIONS Width — in. (mm)	Electric models — cfm (cmm)	215 (6.1)
CGW model — voltage BREAKER/FUSE REQUIREMENTS CEW model — amps CGW model — amps EXHAUST DUCT DIAMETER In. (mm) 4 (101.6) ELECTRONIC BURNER IGNITION CGW model MEATING ELEMENT RATING CGW model — BTU/hr. (kcal/hr.) 24,000 (6,048) CEW model — Electric Heating Element - watts 5,600 GAS INLET CGW model — in. 3/8 N.P.T. ADJUSTABLE LEVELING LEGS APPROXIMATE WEIGHT Crated — lbs. (kg) 163 (73.9) Uncrated — lbs. (kg) DIMENSIONS Width — in. (mm)	ELECTRICAL REQUIREMENTS	
CGW model — voltage BREAKER/FUSE REQUIREMENTS CEW model — amps CGW model — amps EXHAUST DUCT DIAMETER In. (mm) 4 (101.6) ELECTRONIC BURNER IGNITION CGW model MEATING ELEMENT RATING CGW model — BTU/hr. (kcal/hr.) 24,000 (6,048) CEW model — Electric Heating Element - watts 5,600 GAS INLET CGW model — in. 3/8 N.P.T. ADJUSTABLE LEVELING LEGS APPROXIMATE WEIGHT Crated — lbs. (kg) 163 (73.9) Uncrated — lbs. (kg) DIMENSIONS Width — in. (mm)	CEW model — voltage	240V/60Hz
BREAKER/FUSE REQUIREMENTS CEW model — amps CGW model — amps EXHAUST DUCT DIAMETER In. (mm) ELECTRONIC BURNER IGNITION CGW model HEATING ELEMENT RATING CGW model — BTU/hr. (kcal/hr.) CEW model — Electric Heating Element - watts GAS INLET CGW model — in. ADJUSTABLE LEVELING LEGS APPROXIMATE WEIGHT Crated — lbs. (kg) DIMENSIONS Width — in. (mm) 27 (685.8)	CGW model — voltage	
CGW model — amps 15	BREAKER/FUSE REQUIREMENTS	
EXHAUST DUCT DIAMETER In. (mm) 4 (101.6) ELECTRONIC BURNER IGNITION CGW model HEATING ELEMENT RATING CGW model — BTU/hr. (kcal/hr.) 24,000 (6,048) CEW model — Electric Heating Element - watts 5,600 GAS INLET CGW model — in. 3/8 N.P.T. ADJUSTABLE LEVELING LEGS APPROXIMATE WEIGHT Crated — lbs. (kg) 163 (73.9) Uncrated — lbs. (kg) 150 (68) DIMENSIONS Width — in. (mm) 27 (685.8)	CEW model — amps	30
In. (mm) ELECTRONIC BURNER IGNITION CGW model HEATING ELEMENT RATING CGW model — BTU/hr. (kcal/hr.) CEW model — Electric Heating Element - watts GAS INLET CGW model — in. ADJUSTABLE LEVELING LEGS APPROXIMATE WEIGHT Crated — lbs. (kg) Uncrated — lbs. (kg) DIMENSIONS Width — in. (mm) 4 (101.6) 4 (101.6) A (101.6) 14 (101.6) 15 (60,048) 15 (60,048) 15 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048) 16 (60,048)	CGW model — amps	15
ELECTRONIC BURNER IGNITION CGW model HEATING ELEMENT RATING CGW model — BTU/hr. (kcal/hr.) CEW model — Electric Heating Element - watts GAS INLET CGW model — in. ADJUSTABLE LEVELING LEGS APPROXIMATE WEIGHT Crated — lbs. (kg) Uncrated — lbs. (kg) DIMENSIONS Width — in. (mm) Very model — in. 163 (73.9) 163 (73.9) 27 (685.8)	EXHAUST DUCT DIAMETER	
CGW model HEATING ELEMENT RATING CGW model — BTU/hr. (kcal/hr.) CEW model — Electric Heating Element - watts GAS INLET CGW model — in. ADJUSTABLE LEVELING LEGS APPROXIMATE WEIGHT Crated — lbs. (kg) Uncrated — lbs. (kg) DIMENSIONS Width — in. (mm)	In. (mm)	4 (101.6)
HEATING ELEMENT RATING CGW model — BTU/hr. (kcal/hr.) CEW model — Electric Heating Element - watts GAS INLET CGW model — in. ADJUSTABLE LEVELING LEGS APPROXIMATE WEIGHT Crated — lbs. (kg) Uncrated — lbs. (kg) DIMENSIONS Width — in. (mm) 27 (685.8)	ELECTRONIC BURNER IGNITION	
CGW model — BTU/hr. (kcal/hr.) CEW model — Electric Heating Element - watts GAS INLET CGW model — in. ADJUSTABLE LEVELING LEGS APPROXIMATE WEIGHT Crated — lbs. (kg) Uncrated — lbs. (kg) DIMENSIONS Width — in. (mm) 24,000 (6,048) 24,000 (6,048) 24,000 (6,048) 24,000 (6,048) 26,000 16,010 3/8 N.P.T. 163 (73.9) 163 (73.9) 163 (73.9) 27 (685.8)	CGW model	•
CEW model — Electric Heating Element - watts 5,600 GAS INLET CGW model — in. 3/8 N.P.T. ADJUSTABLE LEVELING LEGS APPROXIMATE WEIGHT Crated — lbs. (kg) 163 (73.9) Uncrated — lbs. (kg) 150 (68) DIMENSIONS Width — in. (mm) 27 (685.8)	HEATING ELEMENT RATING	
GAS INLET CGW model — in. 3/8 N.P.T. ADJUSTABLE LEVELING LEGS ● APPROXIMATE WEIGHT (a) Crated — lbs. (kg) 163 (73.9) Uncrated — lbs. (kg) 150 (68) DIMENSIONS 27 (685.8)	CGW model — BTU/hr. (kcal/hr.)	24,000 (6,048)
CGW model — in. 3/8 N.P.T. ADJUSTABLE LEVELING LEGS APPROXIMATE WEIGHT Crated — lbs. (kg) 163 (73.9) Uncrated — lbs. (kg) 150 (68) DIMENSIONS Width — in. (mm) 27 (685.8)	CEW model — Electric Heating Element - watts	5,600
ADJUSTABLE LEVELING LEGS APPROXIMATE WEIGHT Crated — lbs. (kg) Uncrated — lbs. (kg) DIMENSIONS Width — in. (mm) 27 (685.8)	GAS INLET	
APPROXIMATE WEIGHT Crated — lbs. (kg) 163 (73.9) Uncrated — lbs. (kg) 150 (68) DIMENSIONS Width — in. (mm) 27 (685.8)	CGW model — in.	3/8 N.P.T.
Crated — lbs. (kg) 163 (73.9) Uncrated — lbs. (kg) 150 (68) DIMENSIONS 27 (685.8)	ADJUSTABLE LEVELING LEGS	•
Uncrated — lbs. (kg) 150 (68) DIMENSIONS 27 (685.8)	APPROXIMATE WEIGHT	
DIMENSIONS Width — in. (mm) 27 (685.8)	Crated — lbs. (kg)	163 (73.9)
Width — in. (mm) 27 (685.8)	Uncrated — lbs. (kg)	150 (68)
	DIMENSIONS	
	Width — in. (mm)	27 (685.8)
	Depth — in. (mm)	29 (736.6)
Height — in. (mm) 44.80 (1137.92)*		44.80 (1137.92)*

^{*} Height at metercase top does not include pedestal.

See specific instructions for proper installation. Because of continuous product improvement, Whirlpool reserves the right to change specifications without notice. Power cords on electric models sold separately.

LP Conversion Kit #W10135245.

Pedestal Single Box Kit #WHP0400VW Pedestal Pack of 10 Kit #WHP0401VW



Dimensions are for planning purposes only.

See Whirlpool® INSTALLATION INSTRUCTIONS for full details.

MAXIMUM EXHAUST DUCT LENGTH PER NUMBER OF TURNS

TER NOMBER OF TORMS				
Number Of 90° Turns				
	Rigid Metal Vent			

	Rigia Metal vent			
	Box Hood and Louvered Style	Angled Hood Style		
0 1 2 3 4	135 ft. (41.2 m) 125 ft. (38.1 m) 115 ft. (35.1 m) 106 ft. (32.3 m) 98 ft. (29.9 m)	129 ft. (39.3 m) 119 ft. (36.3 m) 109 ft. (33.2 m) 100 ft. (30.5 m) 92 ft. (28.0 m)		

Flexible Metal Vent				
	Box Hood and	Angled Hood		
	Louvered Style	Style		
0	76 ft. (23.2 m)	62 ft. (18.9 m)		
1	71 ft. (21.6 m)	57 ft. (17.4 m)		
2	67 ft. (20.4 m)	53 ft. (16.2 m)		
3	65 ft. (19.8 m)	51 ft. (15.6 m)		
4	63 ft. (19.2 m)	49 ft. (14.9 m)		





NEW YORK CITY M.E.A.







3 YEARS LIMITED PARTS ONLY WARRANTY

For a period from the date of original purchase through the time listed above, the designated parts that fail in normal commercial use will be repaired or replaced free of charge for the part itself, with the owner paying all other costs, including labor, transportation and customs duty. Chemical damage is excluded from all warranty coverage. See complete warranty for details.